## RUST RELEASE FOAMING PENETRATING & CUTTING OIL

This product is designed to be used on farm equipment, sports equipment, industrial equipment, marine and auto equipment. This fast penetrating product lubricates, displaces moisture, frees sticking parts, stops squeaks, stops rust and corrosion and provides long lasting protection.

## DIRECTIONS


Remove protective cap. Point opening in desired direction. Hold container 6-12 inches from surface to be treated. Press button to spray. Spray liberally. Reapply periodically as required.

**DANGER:** Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes eye irritation. May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.



**CONTAINS (CAS#):** Heavy Naphthenic Petroleum Distillate (64742-52-5), Propane/n-Butane (68476-86-8), Mineral Spirits (8052-41-3), Oxygenated Hydrocarbon (N/A).



4408 McLEAN RD • FT. WORTH, TEXAS 76117 CALL TOLL FREE 1-800-359-8031

## **RUST RELEASE**

Multi Purpose Lubricant Frees Sticking Parts Stops Squeaks Seeks Friction

DANGER: EXTEMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

See Additional Cautions on Back Panel

NET WT. 16 OZ. (454 g)