



LUBRI-GUARD

Open Gear Lubricant

For Open Gears, Chains,
Cables, Wire Ropes

Heavy Service Temperature
Range +20°F to +175°F.

Contains No Chlorinated or
Fluorinated Solvents

DANGER: FLAMMABLE
CONTENTS UNDER PRESSURE
KEEP OUT OF REACH OF CHILDREN
See Additional Cautions on Back Panel

NET WT. 12 OZ. (340 g)

This product is a solid film, highly viscous lubricant for use on gears, chains, cables, wire ropes, sprockets, industrial machinery and heavy construction equipment. Protects against rust and corrosion by repelling water from surfaces. Excellent stretching characteristics allow surfaces to be completely covered with lubricant extending life of machinery and reducing down time and maintenance. Reduces noise and protects gears in case of excessive loads. Effective temperature range of +20°F to +175°F.

DIRECTIONS FOR USE


Shake can well before using. Remove protective cap. Hold can 6 to 8 inches from surfaces to be sprayed. Apply an even coat to surface. Turn on machinery and allow lubricant to spread over all working surfaces. Apply a second thinner coating to insure adequate lubrication. Reapply as needed to lubricate and protect equipment. After spraying, turn can upside down and spray until nozzle is clear.

DANGER: Flammable. Contents under pressure. Do not puncture or incinerate container. Do not use or store near heat or open flame. Exposure to temperatures above 120°F may cause bursting. Avoid breathing spray mist. Do not expose to eyes. If in eyes, flush thoroughly with water for 15 minutes.

CONTAINS (CAS#): Petroleum Resin (64742-16-1), Heptane (142-82-5), Propane/n-Butane (68476-86-8), Hydrotreated Petroleum Oils (64742-57-0).

Made in USA

HEALTH	1
FLAMMABILITY	3
REACTIVITY	1
PERSONAL	B



STOCK #30A80I



To Re-Order

PIC
4408 McLEAN • FT. WORTH, TEXAS 76117
CALL TOLL FREE 1-800-359-8031

Proof your labels carefully.

Date: 4/16/12

Account: 185

Product No. 542000013

Ink Color: V24 Black

Cap Color: White

Customer Signature _____

Date _____