

DRY LUBRICANT SPRAY

- Cleaner application
- Resists dust and abrasive particles
- Withstands water, oils, alkalies, and most acids
- Will not wipe off easily-chemically attracted to metal
- Permits immediate use of chain or gear after application
- Will not run off part to which applied, requires less frequent lubrication
- Can be used at higher temperatures and will not carbonize

RECOMMENDED FOR

- CHAIN AND SPROCKET LUBRICATION
- LATHE BED AND RAILS
- REDUCTION OF SLIDING FRICTION
- MACHINE SHOPS
- DOOR LOCKS & HINGES
- RELEASE AGENT

DIRECTIONS FOR USE

Shake can well before using. Clean surface thoroughly. Hold can 6 to 8 inches from surface and apply a thin, even film. Thick coats decrease efficiency. Allow 1 to 5 minutes for adequate drying. The concentration of solids in this product may clog nozzle. Shake vigorously and often. Before storing, turn can upside-down and spray until clear.

Caution: Contains methylene chloride, which has been shown to cause cancer in certain laboratory animals. Risk to your health depends on level and duration of exposure.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; May explode if heated. Causes skin and serious eye irritation. Suspected of causing cancer. May cause respiratory irritation, drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wear protective gloves and eye protection. Wash hands thoroughly after handling. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Avoid breathing mist, fumes, or spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Dispose of contents and container in accordance with local, state, and national regulations.



WARNING: This product can expose you to chemicals including Dichloromethane, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

CONTAINS (CAS#): Methylene Chloride (75-09-2), Propane/n-Butane (68476-86-8), Isopropyl Alcohol (67-63-0), Molybdenum Disulfide (1317-33-5), Organophilic Clay (N/A).

HMIS Ratings: Health-3, Flammability-3, Reactivity-1, Personal-B. Made in USA

STOCK #30A87G

To Re-Order

PIC

4408 GLENVIEW DR • HALTOM CITY, TX 76117
CALL TOLL FREE 1-800-359-8031

PIC

SLICK-N-DRY

Dry Lubricant Spray

Reduces Friction — Retards Wear

Temperature Range
-40°F to +600°F

Molybdenum Disulfide &
Graphite

DANGER:
EXTREMELY FLAMMABLE AEROSOL.
CONTAINS GAS UNDER PRESSURE;
MAY EXPLODE IF HEATED.

NET WT. 12 OZ. (340 g)