

PROTECTS ALL

A flexible, weldable, metal parts protector. When applied, it will prevent rust and corrosion on all metal parts. Apply to machined parts, dies, pipe threads, casting, tools, jigs and stamped metal parts. Prevents corrosion due to salt spray on cables, hoists, pulleys, winches and riggings. Effective in protecting metal parts on boats, ships and dock equipment. Affords long term protection for indoor or outdoor storage. Excellent for protecting materials while in transit. This product is USDA authorized.

A 2 or 3 mil coating will provide indefinite protection for indoor storage and 6 months to 1 year protection for outdoor storage. A 5 or 6 mil coating will protect materials for up to 2 years in outdoor storage. Film is a transparent amber, easy to see through. Can be removed by washing with kerosene or mineral spirits. Once removed, parts can be painted.

DIRECTIONS FOR USE: Product is most effective when parts are clean and free of rust, scale or dirt. However, product will afford adequate protection when applied over rust, scale and dirt, and will aid in removal later. Remove protective cap. Point opening in spray tip towards part to be coated. Holding can 8 to 10 inches from part, spray 2 or 3 mil coat with a slow sweeping motion. Completely wet surface. For extremely severe conditions, wait 5 minutes and apply another coat. Product will completely set up in 2 hours. Once the film is hard, part can be handled. Dust and dirt can be wiped off without affecting film.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure: May explode if heated. Causes skin

and serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.

WARNING: This product can expose you to chemicals including Ethylbenzene, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

CONTAINS (CAS#): Mineral Spirits (8052-41-3), Oxygenated Hydrocarbon (N/A), Propane/n-Butane (68476-86-8), Heptane (142-82-5). Made in USA

HEALTH	1
FLAMMABILITY	3
REACTIVITY	1
PERSONAL	B



STOCK #30A90G



To Re-Order
PIC

4408 Glenview Dr. • Haltom City, TX 76117
CALL TOLL FREE 1-800-359-8031

PIC

PROTECTS ALL Metal Protectant

Prevents Rust & Corrosion
Weldable

Meets Mil Spec C-16173D,
Grade 4 & C83933A

Contains No Chlorinated or
Fluorinated Solvents

DANGER:
EXTREMELY FLAMMABLE AEROSOL.
CONTAINS GAS UNDER PRESSURE;
MAY EXPLODE IF HEATED.

NET WT. 12.5 OZ. (354 g)