

LIGHTNING GREASE

Multi-Purpose Lubricates Penetrates Prevents Rust

DANGER: FLAMMABLE
VAPOR HARMFUL. CONTENTS UNDER PRESSURE
KEEP OUT OF REACH OF CHILDREN
See Additional Cautions on Back Panel

NET WT. 15 OZ. (425 g)

LIGHTNING GREASE

Contains a high temperature, non-melting inorganic red grease. Sprays out as thick liquid, which sets up to a grease in one to two minutes. Penetrates, lubricates and prevents corrosion on all metal parts. Use on chains, winches, conveyors, gears, cable, tools and rollers. For use in cars, boats, buses, warehouses, motors, trucks, industrial plants, automobile dealerships, tractors, hotels, motels, restaurants, schools and in the home. Contains a high pressure additive which reduces wear and prolongs operational life of all machinery. Prevents seizing of threads, loosens up frozen parts and prevents corrosion and rust.

DIRECTIONS FOR USE

Shake well before using. Remove protective cap. Point opening in spray tip towards area to be sprayed. For hard to reach areas insert red extender tube into hole in tip. Apply a light coat by spraying in quick, short bursts. Work part to distribute product evenly over entire surface. Reapply if full coverage is not obtained at first.

DANGER: Flammable. Vapor harmful. Contents under pressure. Do not puncture or incinerate container. Do not use or store near heat or open flame. Exposure to temperatures above 120°F may cause bursting. Contains perchloroethylene. Avoid breathing spray mist. Do not expose to eyes. If in eyes, flush thoroughly with water for 15 minutes. Use only in well ventilated areas. Avoid contact with skin.

INGREDIENTS (CAS#): Heptane (142-82-5), Heavy Naphthenic Petroleum Distillate (64742-52-5), Propane/n-Butane (68476-86-8), Tetrachloroethylene (127-18-4), Organophilic Clay (N/A).

Made in USA

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

	HEALTH	2	
	FLAMMABILITY	3	
	REACTIVITY	0	
	PERSONAL	В	

NFPA



Enviro-mate Series

STOCK #70A611

PIC 4408 McLEAN • FT. WORTH, TEXAS 76117 CALL TOLL FREE 1-800-359-8031