

# SUPER TRANSMISSION CLEANER

## **HOT VAT OR JET SPRAY FOR TRANSMISSIONS**

**EXTRA HEAVY DUTY**

### **CAUTION:**

Irritant. Harmful if swallowed. Carefully read all cautions.

|              |                     |                 |
|--------------|---------------------|-----------------|
| <b>77D57</b> | <b>NET CONTENTS</b> | <b>POUND(S)</b> |
|--------------|---------------------|-----------------|

**TO REORDER  
PIC**

4408 Glenview Dr  
Haltom City, TX 76117  
817-281-1474      1-800-359-8031

Super Transmission Cleaner is a medium duty alkaline detergent specifically designed for cleaning aluminum and other metal surfaces. It is safe, odorless, non-toxic, non-caustic, non fuming and completely soluble. Super Transmission Cleaner cleans by complete and thorough chemical and physical action, as it penetrates and emulsifies oil, grease and other soils to instantly free the surface from contamination. Super Transmission Cleaner is highly recommended for use in spray operations, industrial washing machines and other agitated cleaning units. Super Transmission Cleaner has special additives to prevent rust and corrosion after cleaning.

### **DIRECTIONS:**

For hot soaker tank: 4 to 8 oz of Super Transmission Cleaner per gallon of water should be used. Maintain the temperature as close to boiling as possible. For cleaning grease and oil from metal parts, use 4 to 8 oz per gallon of water at temperatures of 180 to 200 degrees F. The immersion time will vary, depending upon the degrees of contamination, usually from 30 minutes up to 4 hours. To maintain maximum efficiency, it is always advisable to clean the vat periodically. NOTE: Excessive cleaning time, concentrations and temperatures should be avoided as metal attack could occur.

### **CAUTION:**

Active alkaline material, although it is safe to the user, extended skin contact should be avoided to prevent defatting of the skin. In case of eye contact, flush with large amounts of water.