



HI-TEMP RED MULTI-PURPOSE GREASE

81L26

USES

Automotive	Farms
Bottling Plants	Cotton Gins
Sugar Cane Mills	Dairies
Paper Mills	Industrial
Marine	Oil Fields
Steel Mills	Air Conditioning
Elevators	Textile Plants
Construction	Mining
Aircraft	Lumber Mills
Cement Plants	Food Plants
Sewage Plants	

EFFECTS OF OVER EXPOSURE:

EYES: May cause irritation.

SKIN: Repeated or prolonged contact may cause irritation and/or dermatitis.

INHALATION: No adverse effect.

INGESTION: May cause gastrointestinal disturbances such as nausea, vomiting and diarrhea.

EMERGENCY FIRST AID PROCEDURES:

EYES: Wipe and then flush with water. If oily film persists, seek medical aid.

SKIN: Wash contact area with soap and water.

INHALATION: No adverse effects.

INGESTION: No adverse effects. If greater than 1/2 pint is ingested, seek medical aid. DO NOT

INDUCE VOMITING TO AN UNCONSCIOUS

PERSON.

KEEP OUT OF REACH OF CHILDREN.

**PUMP IN HI-TEMP RED GREASE UNTIL ALL
OLD GREASE COMES OUT.**

1/80

Manufactured For

PIC, INC.

P.O. BOX 161577

FORT WORTH, TX 76161

(817) 624-4708 ■ (800) 359-8031

DESCRIPTION

HI-TEMP RED GREASE is an all purpose non-melt grease specially formulated with extreme pressure and anti-wear additives to provide heavy duty service. It is one of very few greases that is able to withstand heavy shock load and impact pressures of 50 Timken load capabilities. This product has excellent adhesive and cohesive properties. It resists most acids, weather, dirt, salt spray, steam and oxidation. Our product protects equipment indoors or outdoors even under high temperatures and heavy loads.

USER BENEFITS

1. Exceptional resistance to acids, water, salt spray, weather, dirt, dust, steam and oxidation.
2. Exceptional adhesive, cohesive and anti-wear properties.
3. Gives extra "cushioning" that reduces shock and noise.
4. Performs at a wide variety of temperatures up to 550° F.
5. Excellent outdoor, extreme pressure and high heat resistance. Water resistant, too.
6. High shock and impact resistant. Won't pound out or thin out.
7. Seals out dust, dirt and contaminants and prolongs the life of metal parts.
8. Contains special corrosion and rust inhibitors.
9. Excellent load carrying capacity: 50 Timken load.